











Dimensions: Millimetres [Inches]
Estimated weight: 1,05 kg (2,31 lbs)

TITLE:
201-011KLST
3nm Masthead
On a 400-035 Promount base, Cable Down

DRAWING No.: 201-011KLST				Sheet No.: 2	DRAWN BY: LSA
SCALE: 1 : 2	SIZE: A3	REV. NO.:	TOLERANCES: DS/ISO 2768-f	REVIEWED BY:	CREATION DATE: 23-07-2024
MATERIAL DESCRIPTION: Alu. EN6082, Acrylic				(20µ) Silver anodized according to EN ISO 7599 (50µ) Black anodized according to MIL-A 8625F	

This Drawing, and the information within, is the property of Lopolight ApS and may not be used in any form without express permission there from. Lopolight reserves the right to change this drawing and assumes no liability for the information communicated herein. Use of dimensions and other information in this drawing is at the users own risk.




LOPOLIGHT

Lopolight ApS
Bakkegaardsvej 513
DK-3050, Humlebaek
Denmark
www.lopolight.com

Tel:(+45) 32 48 50 30
info@lopolight.com

50MM AT A3




Dimensions: Millimetres [Inches]
Estimated weight:1,14 kg (2,51 lbs)


TITLE: 201-011KLST 3nm Masthead On a 400-034 Promount base and 400-404 PE base plate, Cable Side					
DRAWING No.: 201-011KLST				Sheet No.: 3	DRAWN BY: LSA
SCALE: 1 : 2	SIZE: A3	REV. NO.:	TOLERANCES: DS/ISO 2768-f	REVIEWED BY:	CREATION DATE: 23-07-2024
MATERIAL DESCRIPTION: Alu. EN6082, Acrylic, PE					
(20µ) Silver anodized according to EN ISO 7599 (50µ) Black anodized according to MIL-A 8625F					
This Drawing, and the information within, is the property of Lopolight ApS and may not be used in any form without express permission there from. Lopolight reserves the right to change this drawing and assumes no liability for the information communicated herein. Use of dimensions and other information in this drawing is at the users own risk.					

LOPOLIGHT

Lopolight ApS
Bakkegaardsvej 513
DK-3050, Humlebaek
Denmark
www.lopolight.com

Tel:(+45) 32 48 50 30
info@lopolight.com






Dimensions: Millimetres [Inches]
Estimated weight:1,13 kg (2,49 lbs)

TITLE: 201-011KLST 3nm Masthead On a 400-034 Promount base and 400-040 PE base plate, Cable Down					
DRAWING No.: 201-011KLST				Sheet No.: 5	DRAWN BY: LSA
SCALE: 1 : 2	SIZE: A3	REV. NO.:	TOLERANCES: DS/ISO 2768-f	REVIEWED BY:	CREATION DATE: 23-07-2024
MATERIAL DESCRIPTION: Alu. EN6082, Acrylic, PE					

LOPOLIGHT

Lopolight ApS
Bakkegaardsvej 513
DK-3050, Humlebaek
Denmark
www.lopolight.com

Tel:(+45) 32 48 50 30
info@lopolight.com




Dimensions: Millimetres [Inches]
Estimated weight:1,07 kg (2,35 lbs)

TITLE: 201-011KLST 3nm Masthead On a 400-034 Promount base and 400-404 PE base plate, Cable Down					
DRAWING No.: 201-011KLST				Sheet No.: 6	DRAWN BY: LSA
SCALE: 1 : 2	SIZE: A3	REV. NO.:	TOLERANCES: DS/ISO 2768-f	REVIEWED BY:	CREATION DATE: 23-07-2024
MATERIAL DESCRIPTION: Alu. EN6082, Acrylic, PE					
(20µ) Silver anodized according to EN ISO 7599 (50µ) Black anodized according to MIL-A 8625F					
This Drawing, and the information within, is the property of Lopolight ApS and may not be used in any form without express permission there from. Lopolight reserves the right to change this drawing and assumes no liability for the information communicated herein. Use of dimensions and other information in this drawing is at the users own risk.					

LOPOLIGHT

Lopolight ApS
Bakkegaardsvej 513
DK-3050, Humlebaek
Denmark
www.lopolight.com

Tel:(+45) 32 48 50 30
info@lopolight.com



65,63 [2,58]

125,5 [4,94]
103,5 [4,07]
77,5 [3,05]
35 [1,38]
14 [0,55]
0 [0]

2,42 [0,1]
5,83 [0,23]
White 225°
CL

3X120°
Ø130 [Ø5,12]
Ø111,2 [Ø4,38]
Mounting holes
3XØ6,1 [Ø0,24]

Dimensions: Millimetres [Inches]
Estimated weight:1,27 kg (2,8 lbs)

TITLE: 201-011KLST 3nm Masthead On a 400-037 Promount base and 400-404 PE base plate , Cable Side					
DRAWING No.: 201-011KLST				Sheet No.: 7	DRAWN BY: LSA
SCALE: 1 : 2	SIZE: A3	REV. NO.:	TOLERANCES: DS/ISO 2768-f	REVIEWED BY:	CREATION DATE: 23-07-2024
MATERIAL DESCRIPTION: Alu. EN6082, Acrylic, PE (20µ) Silver anodized according to EN ISO 7599 (50µ) Black anodized according to MIL-A 8625F					
This Drawing, and the information within, is the property of Lopolight ApS and may not be used in any form without express permission there from. Lopolight reserves the right to change this drawing and assumes no liability for the information communicated herein. Use of dimensions and other information in this drawing is at the users own risk.					

LOPOLIGHT
Lopolight ApS
Bakkegaardsvej 513
DK-3050, Humlebaek
Denmark
www.lopolight.com
Tel:(+45) 32 48 50 30
info@lopolight.com