









Dimensions : Millimetres [Inches]
Estimated weight: 1,38 kg (3,04 lbs)

TITLE:
300-112G2ST+301-140 / 301-112ST+301-140
 3nm 360° White, Dbl + 60° Panama Steering via RPM
 On a 400-035 Promount base, 400-404 PE base plate, Cable Down

DRAWING No.: 300-112G2ST+301-140 / 301-112ST+301-140				Sheet No.: 1		DRAWN BY: LSA	
SCALE: 1 : 2		SIZE: A3		REV. NO.:		TOLERANCES: DS/ISO 2768-f	
REVIEWED BY:				CREATION DATE: 15-11-2023			
MATERIAL DESCRIPTION: Alu. EN6082, Acrylic							
(25p) Silver anodized according to EN ISO 7599 (50p) Black anodized according to MIL-A 8625F							


This Drawing, and the information within, is the property of Lopolight ApS and may not be used in any form without express permission there from. Lopolight reserves the right to change this drawing and assumes no liability for the information communicated herein. Use of dimensions and other information in this drawing is at the users own risk.







LOPOLIGHT

Lopolight ApS
Bakkegaardsvej 513
DK-3050, Humlebaek
Denmark
www.lopolight.com

Tel:(+45) 32 48 50 30
info@lopolight.com





TITLE:
300-112G2ST+301-140 / 301-112ST+301-140
3nm 360° White, Dbl + 60° Panama Steering via RPM
On a 400-035 Promount baseand, Cable Down

SCALE:
1 : 2

LOPOLIGHT

Tel:(+45) 32 48 50 30
info@lopolight.com

