



1nm starboard, black anodized

101-001-B

1nm stbd, silver anodized

- LED (Light Emitting Diode) navigation light.
- Unique and precise definition of light angles.
- Rugged and unbreakable
- Vertically mounted with 2,5m cable
- 5 years warranty

Specifications	
Number	101-001-B
Light Color	NULL
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	NULL
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	NULL
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010284
IP rating	IP68
Power draw (W)	1,1
UPC Code	879343010287
Connection	2.5m cable

Specifications

Current consumption (mA @ 12VDC)	66
-------------------------------------	----

Current consumption (mA @ 24VDC)	34
-------------------------------------	----

Vessel size	Under 12M
-------------	-----------

Min. feed wire gauge	0.5mm2 AWG22
----------------------	--------------

Weight (Kg)	0.39 Kg
-------------	---------

Weight (Oz)	13.76 Oz
-------------	----------