



1nm port, black anodized

101-002-B 6M

1nm port, black anodized

Vertically mounted with 6m cable

Specifications

Number 101-002-B 6M

Light Color Red

Dimensions metric 92,5 x 28 x 49,7

Certification This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under [Support](#)

Intensity >1.2cd

Dimensions imperial 3.6" x 1.1" x 1.95"

Approved to COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR

Visibility 1nm

Included In Package 1 Navigation light,Installation guide

Operating temperature -25°C to 55°C

Mounting Vertical

Materials Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane

Operating Voltage 10-32VDC

EAN 5704438016194

IP rating IP68

Power draw (W) 1,1

UPC Code 879343016203

Connection 6m cable

Specifications

**Current consumption
(mA @ 12VDC)** 60

**Current consumption
(mA @ 24VDC)** 32

Vessel size Under 12M

Min. feed wire gauge 0.5mm² AWG22

Weight (Kg) 0.6 Kg

Weight (Oz) 21.16 Oz