



1nm port, black anodized

101-002-B

1nm port, black anodized
Vertically mounted with 2,5m cable

Specifications	
Number	101-002-B
Light Color	Red
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>1.2cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light, precabled with 2.5 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438009943
IP rating	IP68
Power draw (W)	1,1
UPC Code	879343009946
Connection	2,5m cable

Specifications

**Current consumption
(mA @ 12VDC)** 60

**Current consumption
(mA @ 24VDC)** 32

Vessel size Under 12M

Min. feed wire gauge 0.5mm² AWG22

Weight (Kg) 0.39 Kg

Weight (Oz) 13.76 Oz