



1nm port, silver anodized

101-002

1nm port, silver anodized

Vertically mounted with 2,5m cable

Specifications

Number 101-002

Light Color Red

Dimensions metric 92,5 x 28 x 49,7

Certification This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under [Support](#)

Intensity >1.2cd

Dimensions imperial 3.6" x 1.1" x 1.95"

Approved to COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR

Visibility 1nm

Included In Package 1 Navigation light, precabled with 2.5 meter shielded marine grade cable, Installation guide

Operating temperature -25°C to 55°C

Mounting Vertical

Materials Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane

Operating Voltage 10-32VDC

EAN 5704438009936

IP rating IP68

Power draw (W) 1,1

UPC Code 879343009939

Connection 2.5m cable

Specifications

Current consumption (mA @ 12VDC)	60
-------------------------------------	----

Current consumption (mA @ 24VDC)	32
-------------------------------------	----

Vessel size	Under 12M
-------------	-----------

Min. feed wire gauge	0.5mm2 AWG22
----------------------	--------------

Weight (Kg)	0.39 Kg
-------------	---------

Weight (Oz)	13.76 Oz
-------------	----------