



5nm Masthead, Double, silver anodized

300-038-CD

5nm dbl masthead, silver anodized

Horizontally mounted on 400-035, cable down base

Specifications

Number 300-038-CD

Light Color White

Dimensions metric Ø92,5mm x 128mm

Certification This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under [Support](#)

Intensity >52cd

Dimensions imperial Ø3.6" x 5"

Approved to COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR

Visibility 5nm

Operating temperature -25°C to 55°C

Mounting Horizontal

Materials Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane

Operating Voltage 20-32VDC

EAN 5704438006393

IP rating IP68

Power draw (W) 7

UPC Code 879343006396

Connection Plug connector

Current consumption (mA @ 12VDC) 0

Specifications

Stock status	Usually in stock
--------------	------------------

Current consumption (mA @ 24VDC)	290
-------------------------------------	-----

Vessel size	20-50M
-------------	--------

Min. feed wire gauge	0.5mm2 AWG22
----------------------	--------------

Weight (Kg)	1.45 Kg
-------------	---------

Weight (Oz)	51.14 Oz
-------------	----------