



6nm Masthead, Double, silver anodized

300-138-CD

6nm dbl masthead, silver anodized
Horizontal mounted on (400-035) CD base.

Specifications	
Number	300-138-CD
Light Color	White
Dimensions metric	Ø92,5mm x 128mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>94cd
Dimensions imperial	Ø3.6" x 5"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	6nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438007086
IP rating	IP68
Power draw (W)	13
UPC Code	879343007089
Connection	Plug connector
Current consumption (mA @ 12VDC)	0

Specifications

**Current consumption
(mA @ 24VDC)** 580

Vessel size Over 50M

Min. feed wire gauge 0.5mm² AWG22

Weight (Kg) 1.45 Kg

Weight (Oz) 51.14 Oz