



2nm stern light w/6W decklight , silver anodized

301-006DLX

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.

Vertical mounted with 2,5 meter cable
Stern light and deck light have a 2 lead power cable each.

Specifications	
Number	301-006DLX
Light Color	White
Dimensions metric	86 x 50 x 59
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	3.3" x 1.9" x 2.27"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438011588
IP rating	IP68
Power draw (W)	1,3
UPC Code	879343011581
Connection	2.5m cable

Specifications

**Current consumption
(mA @ 12VDC)** 110

Stock status Usually in stock

Lead time 1-2 weeks

**Current consumption
(mA @ 24VDC)** 50

Vessel size Under 12M,12-20M,20-50M

Min. feed wire gauge 0.5mm2 AWG22

Weight (Kg) 0.66 Kg

Weight (Oz) 23.28 Oz