



5nm masthead+6W decklight, black anodized

301-011DLX-B 15M

5nm masthead+6W decklight, black anodized
Vertical mounted with 15m cable

Specifications	
Number	301-011DLX-B 15M
Light Color	White
Dimensions metric	54 x 38,7 x 72,2
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>52cd
Dimensions imperial	2.1" x 1.5" x 2.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438013063
IP rating	IP68
Power draw (W)	4,1
UPC Code	879343013066
Connection	15m cable

Specifications

**Current consumption
(mA @ 12VDC)** 320

Stock status Made to order

**Current consumption
(mA @ 24VDC)** 170

Vessel size 20-50M

Min. feed wire gauge 0.5mm2 AWG22

Weight (Kg) 1.25 Kg

Weight (Oz) 44.09 Oz